

# Specifications — DVI DA2

---

**NOTE** \*Appropriate DVI-D to HDMI cables or adapters are required for HDMI signal input/output.

## Video

Maximum bit rate.....	4.95 Gbps (1.65 Gbps per color)
Maximum pixel clock.....	165 MHz
Resolution range.....	Up to 1920x1200 or 1080p @ 60 Hz
Formats.....	RGB and YCbCr digital video
Standards.....	DVI 1.0, HDMI 1.2

## Video input

Number/signal type.....	1 single link DVI-D (or HDMI*)
Connectors.....	1 female DVI-I

## Video output

Number/signal type.....	2 single link DVI-D (or HDMI*): 1 main, 1 local
-------------------------	---

**NOTE** Local output is used for DDC communications and hot plug detection.

Connectors.....	2 female DVI-I
-----------------	----------------

## General

External power supply.....	100 VAC to 240 VAC, 50/60 Hz, external; to 12 VDC, 1 A, regulated
Power input requirements.....	12 VDC, 0.4 A
Temperature/humidity.....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling.....	Convection, no vents
Mounting	
Rack mount.....	Yes, with optional 1U, 9.5" deep rack shelf (RSU 129, #60-190-01; RSB 129, 60-604-01); 1U, 6" deep rack shelf (RSU 126, #60-190-10; RSB 126, 60-604-10); or 1U, 3.5" deep VersaTools® rack shelf (RSF 123, #60-190-20; RSB 123, 60-604-20)
Furniture mount.....	Yes, with optional MBU 125 Under Desk Mounting Kit, #70-077-01
Enclosure type.....	Metal
Enclosure dimensions.....	1.75" H x 8.75" W x 3.0" D (1U high, half rack wide) (4.4 cm H x 22.2 cm W x 7.6 cm D) (Depth excludes connectors.)
Product weight.....	2.8 lbs (1.3 kg)
Shipping weight.....	5 lbs (3 kg)
Vibration.....	ISTA 1A in carton (International Safe Transit Association)
Listings.....	UL, CUL
Compliances.....	CE, FCC Class A, VCCI, AS/NZS, ICES
MTBF.....	30,000 hours
Warranty.....	3 years parts and labor

**NOTE** All nominal levels are at  $\pm 10\%$ .

**NOTE** Specifications are subject to change without notice.

7.6-042108-D6